

Product Name: A7 Adhesive**Date prepared:** July, 2007**Description:** **Part A:** Methacrylate Adhesive **Part B:** Peroxide Activator**Manufacturer:** ITW Red Head · 2171 Executive Drive, Suite 100 · Addison, IL 60101**Emergency Number:** 1-800-424-9300**Ingredients and Exposure Limits**

Ingredients	CAS Number	TLV: (mg/m ³)	PEL: (mg/m ³)	STEL
Part A: Methyl Methacrylate	80626	100 ppm	100 ppm	100 ppm
Part B: Dibutyl Phthalate	84742	5 mg/m ³	5 mg/m ³	5 mg/m ³
Benzoyl Peroxide	94360	5 m/m ³	5 mg/m ³	5 ppm

Abbreviations: TLV = ACGIH Threshold Limit Value PEL = OSHA Permissible Exposure STEL = Short Term Exposure Limit
NA = Not Applicable NE = None Established

Physical Properties

Properties	Part A: Beige Paste	Part B: Gray Paste
Specific Gravity	= 1.60 g/cm ³ (at 20° C)	= 1.60 g/cm ³ (at 20° C)
Boiling Point	= > 213° F	NE
Water Solubility	None	None

Safe Handling Procedures

Handling Precautions: Keep away from children. Do not get in eyes, skin or on clothing. Wash thoroughly after handling. Avoid breathing vapors. Use only as directed; avoid uncontrolled mixing with other materials, esp. polymerizable or combustible materials.

Storage: For maximum shelf life, store in cool dry area between 40° to 80° F. Do not store above 110° F. Keep away from heat, sparks, open flame. Exposure to high heat can cause violent reaction. Do not store near combustibles.

Spill Procedures: Collect with an absorbent material and place in a container for proper disposal. For large spills, transfer to salvage vessels, and dispose of according to state, local and Federal regulations. Flush area with water to remove residue.

Personal Protection

Ventilation: Use in well ventilated areas. Provide mechanical ventilation in enclosed areas.

Eye protection: Wear safety glasses with side shields.

Skin protection: Impervious butyl rubber gloves recommended.

Respiratory protection: None normally required with normal ventilation. Where ventilation is inadequate to control vapors, use a NIOSH/MSHA air purifying system with an organic vapor cartridge.

Health Information

Signs and Symptoms of Exposure: Inhalation can cause headache, nausea, dizziness, fatigue, and drowsiness.

Part A: Eye and skin irritant. Possible skin sensitizer.

Part B: Corrosive

Signs and Symptoms of Exposure: Part A: May be irritating to the eyes, skin, nose and throat. May cause skin sensitization. In applications where vapors (caused by high temperatures) or mists (caused by mixing) are created, breathing may cause a mild burning sensation in the nose, throat and lungs.

Part B: May cause eye and skin burns. Vapors may be irritating. May cause burns if swallowed.

Medical Conditions Aggravated by Exposure: Eye, skin and respiratory conditions.

First Aid Measures

Eyes: Flush immediately with water for at least 15 minutes. Get immediate medical attention.

Skin: Wash immediately with soap and water. Launder contaminated clothing before reuse.

Inhalation: If symptoms occur, move to fresh air. Seek medical attention if symptoms persist.

Ingestion: Rinse mouth and then drink large quantities of water. Don't give anything by mouth to an unconscious person. Seek medical attention. Do not induce vomiting unless directed by a physician.

Other: Referral to a physician is recommended if there is any question about the seriousness of the exposure.

Stability and Reactivity

Stability: Stable at normal temperatures.

Hazardous Polymerization: Will not occur at normal temperatures.

Incompatibility: Strong acids and oxidizing agents.

Decomposition Products: Thermal decomposition can yield CO_x, NO_x, water and carbon.

Conditions to Avoid: Avoid elevated temperatures which may shorten the shelf-life of this product.
Avoid open flame.

Fire and Explosion Hazard Information

Flash point: 64° F

Flammable Limits in air: Lower: 2.1; Upper: 12.5

Extinguishing Media: CO₂, Dry Chemical and Foam.

Special Fire Fighting Procedures: Keep personnel removed and upwind from fire. Use self-contained breathing apparatus and full protective equipment.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel to ignition sources and flash back.

Hazardous products of combustion: Carbon monoxide, carbon dioxide, trace amount of sulfur compounds and smoke.

Regulatory Information

Hazard Communication: This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

HMIS Codes: Health 2, Flammability 3, Reactivity 2, PPE B

DOT Shipping Name: Consumer commodity, ORM-D

TSCA Inventory Status: Chemical components are listed on TSCA inventory or exempt as impurities.

SARA Title III, Section 313: This product contains Methyl Methacrylate Monomer which is subject to reporting under Section 313 or SARA Title III (40 CFR Part 372).

EPA Waste Code(s): D001

Waste Disposal Methods: Consult with regulatory agencies of your corporate personnel for disposal methods that comply with local, state and federal safety, health and environmental regulations.

Notes: In normal use, the methyl Methacrylate in this product is polymerized during cure. For purposes of air quality regulations, the maximum amount of VOC (i.e. MMA) emitted is negligible (< 5%) Actual emissions are a function of substrate and process and should be considered on an individual basis.

Canadian regulations: WHMIS hazard classes: B2, C, D2A, and D2B

Canadian EPA: All ingredients are listed on the DSL or are exempt as impurities.

The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.